

UVR-M, UV Cleaner–Recirculator

DESCRIPTION

UVR-M is ideal for air disinfection in hospitals (especially in outpatient departments, operating rooms, emergency rooms, delivery rooms etc.), kindergartens, research laboratories, veterinary clinics

The devices provide complete protection from direct ultraviolet radiation.

Recirculators fixation:

- Convenient fixation on walls (standard)
- Mounting on a movable tripod (optional)

SPECIFICATIONS

UV radiation source:	1 lamp - 25W Bactericidal, TUV25WG13 UV-C
UV radiation level	18 mW / cm ² / sec
Air-flow productivity	14 m ³ /hour
Full user protection from direct UV light	+
UV lamp operation indicator	+
Overall dimensions (W×D×H)	110 x 135 x 660 mm
Weight	3.4 kg
Power consumption (230V / 120 V)	125 VA (540 mA) / 160 VA (1.3 A)
Nominal operating voltage	230 V, 50 Hz or 120 V, 60 Hz
---	---
Tripod UVR-S dimensions	600 x 600 x ~1100 mm



CAT. NUMBER

BS-040105-AAA	230VAC 50/60Hz Euro plug
BS-040105-AAB	230VAC 50/60Hz UK plug
BS-040105-AA3	230VAC 50/60Hz AU plug
BS-040105-AAC	120VAC 60Hz US plug
BS-040105-BK	IQ OQ document
BS-040105-CK	PQ document

ACCESSORIES



UVR-S
BS-040105-AK
tripod